

# PRODUCT DATASHEET

## STERIWHITE AIRQ600 R

STERIWHITE AIRQ600 | UVC disinfection of ambient air in rooms with constant occupancy



---

### Product features

- Extremely quiet, no annoying air flow
- Energy-efficient
- Low-maintenance
- Easy operation
- Modern design
- One performance level 600 m<sup>3</sup>/h at <39 dB (A)
- Made in Germany

TECHNICAL DATA

Electrical data

Nominal wattage	300.00 W
Nominal voltage	230 V
Mains frequency	50 Hz
Protection class	I
Operating mode	Integrated driver


UV & Air cleaning

Maximum disinfection volume flow	600 m³/h
Air circulation	600 m³/h
UV radiated power	204 W
UV-C source lifetime	16000 h
Noise level in UV-C disinfection mode	< 39 dB
Suitable for room space up to	70 m²

Dimensions & Weight

Length	315.00 mm <sup>1)</sup>
Width	860.00 mm <sup>1)</sup>
Height	860.00 mm <sup>1)</sup>
Product weight	53000.00 g
Cable length	3000 mm

1) The dimension can vary depending on type of mounting variant



STERIWHITE AIRQ600 R /  
STERIWHITE AIRQ600 W

Materials & Colors

Product color	White
---------------	-------

Body material	Steel
Mercury content	0.0 mg


Application & Mounting

Ambient temperature range	0...+40 °C
Type of connection	Plug type C (EU)
Protection class IK (shock resistance)	IK03
Dimmable	No
Mounting type	Standing
Mounting location	Floor

Certificates & Standards

Standards	CE
-----------	----

DOWNLOAD DATA

Documents and certificates		Document name
	Legal information	Informationstext 18 Abs 4 ElektroG

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.