

# PRODUCT DATASHEET LED ECO DAMPPROOF HOUSING 12X2 WMT

LED ECO DAMPPROOF HOUSING GEN2 WMT | Damp-proof luminaires



#### Areas of application

- Industrial and storage facilities
- Car parks and underpasses
- Garages
- Workshops, assembly lines

### Product benefits

- UV stabilized, impact resistant polycarbonate diffuser and body
- PC clips and stainless-steel clips
- Fused design to offer protection when inserting traditional T8 florescent tubes by mistake
- Designed to work with IEC 62776 compliant LED T8 with AC input on one end

#### **Product features**

- 2 series to choose from: with and without metal tray in the housing
- $\,-\,$  Available with: 2 ft, 4 ft and 5 ft
- 70 mm full height housing design in all models
- Available in 1 lamp & 2 lamps versions
- Type of protection: IP65
- Impact resistance: IK08



#### **TECHNICAL DATA**

# Dimensions & Weight

Length	1261.00 mm
Width	102.00 mm
Height	70.00 mm
Product weight	1390.00 g

LDECO DP 12X2 HOUSING WMT G2

#### Materials & Colors

Product color	Gray
Housing color	Gray
Body material	Polycarbonate (PC)
Mercury content	0.0 mg

# **Application & Mounting**

Type of connection	Terminal, 2-Pole (L, N)
Type of protection	IP65
Protection class IK (shock resistance)	IK08
Dimmable	No
Mounting type	Suspended/Surface
Mounting location	Ceiling / Wall
Replaceable light source	No

# LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075544468	Folding box	110 mm x 79 mm x 1,265 mm	1453.00 g	10.99 dm <sup>3</sup>
4058075544475	Shipping box	1,282 mm x 236 mm x 265 mm	7885.00 g	80.18 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

# DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.