

# PRODUCT DATASHEET LED VALUE LINEAR HIGHBAY 150W 865 HRO

LED VALUE LINEAR HIGHBAY | High-bay luminaires



#### Areas of application

- Factory
- Warehouses
- Distribution centre
- Other high ceiling indoor application

### Product benefits

- Energy savings thanks to system efficacy up to 135 lm/W
- 1-10 dimming provides additional energy saving
- $-3\ kinds of beam\ angle\ available,\ Narrow\ (60°),\ Wide\ (90°)\ and\ High\ rack\ optic\ (30°\times 90°),\ can\ meet\ different\ application\ requirements$
- IP44, can be used in indoor wet environment
- Low maintenance costs thanks to long lifetime 50,000 hrs @ 35 °C

#### **Product features**

- Available in 4 lengths: 252 mm, 491 mm, 730 mm and 969 mm
- Available with wattage: 50 W, 100 W, 150 W and 200 W
- Surge protection: up to 4 kV (L/N-PE), 2 kV (L-N)
- Available in sling suspended and bracket mounted
- Certificate: CB, RoHS

### **TECHNICAL DATA**

### Electrical data

Nominal wattage	150.00 W
Nominal voltage	100240 V
Mains frequency	5060 Hz
Nominal current	1600.000 mA
Max. number of luminaires per miniature circuit breaker B16	2
Max. number of luminaires per miniature circuit breaker C16	2
Power factor $\lambda$	> 0.90
Total harmonic distortion	< 20 %
Protection class	I

### Photometrical data

Luminous flux	19500 lm
Luminous efficacy	130 lm/W
Color temperature	6500 K
Light color (designation)	Daylight
Color rendering index Ra	80
Beam angle	30° x 90°

# Dimensions & Weight

Length	730.00 mm
Width	129.00 mm
Height	70.00 mm
Product weight	2000.00 g



LDVAL LINEAR HB 150W

### Materials & Colors

Product color	Gray
Housing color	Gray
Body material	Aluminum
Glow Wire Test according to IEC 60695-2-12	650 °C
Mercury content	0.0 mg

### **Application & Mounting**

Ambient temperature range	-20+45 °C
Type of connection	Terminal
Type of protection	IP44
Protection class IK (shock resistance)	IK06
Dimmable	Yes
Type of dimming	1-10V
Mounting type	Suspended/Surface
Application environment	Indoor
Mounting length	730 mm
Mounting width	129 mm
With light source	Yes
Replaceable light source	No

### Certificates & Standards

Ball shot safe	No
Replaceable light source (EPREL)	Not replaceable

# Additional product data

Number of illuminants	no
-----------------------	----

# DOWNLOAD DATA

Photometric and lighting design files	Document name
IES file (IES)	LDVAL LINEAR HB 150W 865 HRO

#### LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075660496	Folding box	780 mm x 105 mm x 155 mm	2274.00 g	12.69 dm <sup>3</sup>
4058075660502	Shipping box 6	795 mm x 350 mm x 330 mm	14869.00 g	91.82 dm³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

#### **DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.