

# PRODUCT DATASHEET SMART+ WIFI ORBIS WALL DUPLO IP44 300mm

SMART+ WIFI ORBIS WALL DUPLO | Smart bathroom decorative ceiling and wall with wifi technology IP44 TW and dimmable luminaires

#### Areas of application

- Bathrooms



#### Product benefits

- Easy and quick installation

#### Product features

- Type of protection: IP44
- Controllable via LEDVANCE SMART+ App (with minimum Android 8.0 or iOS 14.0)
- Controllable via voice control available: Google Assistant or Amazon Alexa
- Adjustable color temperature via Tunable White: 3,000...6,500 K
- Dimmable
- Network protocol: WiFi



# **TECHNICAL DATA**

# Electrical data

Nominal wattage	15.00 W
Nominal voltage	220240 V
Mains frequency	5060 Hz
Nominal current	67.000 mA
Inrush current	0.03 A
Inrush current time T <sub>h50</sub>	100 μs
Power factor $\lambda$	> 0.90
Total harmonic distortion	< 20 %
Protection class	II
Operating mode	External LED driver

# Photometrical data

Luminous flux	1100 lm
Total luminous flux of contained light sources	1400 lm
Luminous efficacy	80 lm/W
Color temperature	30006500 K
Reference control setting of contained light source (Kelvin)	3000 K <sup>1)</sup>
Light color (designation)	Tunable White
Color rendering index Ra	> 80
Standard deviation of color matching	< 6 sdcm
Photobiological safety group acc. to EN62778	RG0
Photobiological safety group acc. to EN62471	RG0
Beam angle	110°

<sup>1)</sup> Performing a reset will restore the default values set by the manufacturer

# Dimensions & Weight

Length	295.00 mm
Width	60.00 mm
Height	58.00 mm
Product weight	560.00 g

# SMART WIFI ORBIS DUPLO 300 IP44 TW CR

# Materials & Colors

Product color	Silver
Housing color	Silver
Body material	Acrylonitrile butadiene styrene (ABS)
Cover material	Polycarbonate (PC)
Mercury content	0.0 mg

# **Application & Mounting**

Ambient temperature range	-20+40 °C
Temperature range at storage	-20+80 °C
Type of connection	Screw terminal
Type of protection	IP44
Protection class IK (shock resistance)	IK03
Dimmable	Yes
Type of dimming	WiFi
Mounting type	Surface
Mounting location	Ceiling
Application environment	Indoor
With light source	Yes

# Lifespan

Lifespan L70/B50 at 25 °C	30000 h
Number of switching cycles	15000

# **Emergency lighting**

Type of emergency operation test	None
Integrated test switch	No

# Certificates & Standards

Standards	CE / UKCA	
Luminaire with limited surface temperature, "D sign"	No	
Replaceable light source (EPREL)	Not replaceable	

#### **EQUIPMENT / ACCESSORIES**

- Mounting bracket included
- Mounting screws and dowels included
- Control via app or voice control requires compatible Smart home system
- For control via LEDVANCE SMART+ App, a smartphone or tablet is required (with minimum Android 8.0 or iOS 14.0)

# Safety advice

- Check wall-ceiling for suitability. If uncertain, seek professional advice.
- All electrical connections must be made by a qualified person.
- Caution, risk of electric shock.

#### **DOWNLOAD DATA**

Documents and certificates		Document name	
User instruction / safety instructions		SMART WIFI ORBIS DUPLO	
Legal information Legal insert Residential luminaires		Legal insert Residential luminaires	
PDF	Declarations of conformity	CE Declaration Smart Orbis	
PDF	Declarations of conformity UKCA	ations of conformity UKCA SMART WIFI ORBIS	

#### LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075573659	Folding box	70 mm x 100 mm x 350 mm	640.00 g	2.45 dm <sup>3</sup>
4058075573666	Shipping box 4	366 mm x 156 mm x 218 mm	2870.00 g	12.45 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

#### References / Links

- Further information and frequently asked questions (FAQs) at www.ledvance.com/consumer/smart/faq

# **DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.