

# PRODUCT DATASHEET LED VALUE CLAS A 8.5 W/2700 K E27 GEN4

LED VALUE CLASSIC A | LED lamps, classic bulb shape



#### Areas of application

- Domestic applications
- General illumination
- Outdoor applications only in suitable luminaires

## Product benefits

- No "Blue Light" Hazard (according to IEC62778)
- Photobiological safety according to IEC 62778, risk group RG0
- Energy savings of up to 85 % (compared to traditional incandescent lamps)
- Instant 100 % light, no warm-up time
- No UV and near-IR radiation in the light beam
- Reliable operation thanks to brand quality

#### **Product features**

- Color rendering index  $R_a$ ;  $\ge 80$
- Not dimmable
- Mercury-free lamps



## TECHNICAL DATA

### Electrical data

| Nominal wattage                        | 8.5 W    |
|--|----------|
| Construction wattage                   | 8.50 W   |
| Nominal voltage                        | 220240 V |
| Claimed equiv. conventional lamp power | 60 W     |
| Nominal current                        | 67 mA    |
| Type of current                        | AC       |
| Operating frequency                    | 50/60 Hz |
| Mains frequency                        | 50/60 Hz |
| Power factor $\lambda$                 | > 0.50   |

### Photometrical data

| Luminous flux                           | 806 lm     |
|---|------------|
| Nominal useful luminous flux 90°        | 806 lm     |
| Luminous efficacy                       | 94 lm/W    |
| Lumen main.fact.at end of nom.life time | 0.70       |
| Light color (designation)               | Warm White |
| Color temperature                       | 2700 K     |
| Color rendering index Ra                | ≥80        |
| Light color                             | 827        |
| Standard deviation of color matching    | ≤6 sdcm    |
| Rated LLMF at 6,000 h                   | 0.80       |

## Light technical data

| Beam angle          | 180 °    |
|---------------------|----------|
| Warm-up time (60 %) | < 0.50 s |
| Starting time       | < 0.5 s  |

## **Dimensions & Weight**

| Overall length   | 113.00 mm |
|------------------|-----------|
| Diameter         | 60.00 mm  |
| Maximum diameter | 60 mm     |
| Product weight   | 28.00 g   |

# Temperatures & operating conditions

# Lifespan

| Number of switching cycles                   | 100000 |
|--|--------|
| Lumen maintenance at end of service lifetime | 0.70   |
| Rated lamp survival factor at 6,000 h        | ≥ 0.90 |

# Additional product data

| Base (standard designation) | E27  |
|-----------------------------|--|
| Mercury content             | 0.0 mg   |
| Mercury-free                | Yes  |
| Product remark              | All technical parameters apply to the entire lamp / Due to the complex<br>production process for light-emitting diodes, the typical values shown<br>for the technical LED parameters are purely statistical values that do<br>not necessarily match the actual technical parameters of each<br>individual product, which can vary from the typical value |

### Capabilities

| Dimmable No |
|-------------|
|-------------|

## Certificates & Standards

| Energy efficiency class                      | F <sup>1)</sup> |
|--|-----------------|
| Energy consumption                           | 9.00 kWh/1000h  |
| Photobiological safety group acc. to EN62778 | RG0             |

1) Energy efficiency class (EEC) on a scale of A++ (highest efficiency) to E (lowest efficiency)

# Country-specific categorizations

# Energy labelling regulation data acc EU 2019/2015

| Light source cap-type (or other electric interface) | E27          |
|---|--------------|
| Correlated colour temperature type                  | SINGLE_VALUE |
| Length  | 113.00 mm    |
| Height  | 60.00 mm     |
| Width   | 60.00 mm     |
| EPREL ID  | 1403215      |
| Model number  | AC24699      |

## DOWNLOAD DATA

| Photometric and lighting design files |  |  |
|---------------------------------------|--|--|
|                                       |  |  |

Document name

IES file (IES)

LED VALUE CLA60 8.5W 2700K

### LOGISTICAL DATA

ES )

| Product code  | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume               |
|---------------|------------------------------|--------------------------------------|--------------|----------------------|
| 4058075202023 | Folding box<br>1             | 61 mm x 61 mm x 110 mm               | 55.00 g      | 0.41 dm <sup>3</sup> |
| 4058075351448 | Shipping box<br>10           | 318 mm x 132 mm x 130 mm             | 504.00 g     | 5.46 dm <sup>3</sup> |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

#### DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.