

PRODUCT DATASHEET LED ECO CLAS A 7 W/6500 K B22d GEN5

LED ECO CLASSIC A | LED lamps, classic bulb shape



Areas of application

- Suitable for indoor applications.

Product benefits

- Energy savings of up to 88 % (compared to traditional incandescent lamps)
- Excellent price/performance ratio
- No UV and near-IR radiation in the light beam
- Reliable operation thanks to brand quality

Product features

- Base: E27, B22d
- Luminous efficacy: up to 100 lm/W
- Mercury-free lamps
- Lifetime: up to 12,000 h
- Overtemperature protection



TECHNICAL DATA

Electrical data

Nominal wattage	7 W
Construction wattage	7.00 W
Nominal voltage	220240 V
Claimed equiv. conventional lamp power	60 W
Nominal current	54 mA
Type of current	AC
Operating frequency	5060 Hz
Mains frequency	5060 Hz
Power factor λ	0.50

Photometrical data

Luminous flux	560 lm
Nominal useful luminous flux 90°	560 lm
Luminous efficacy	80 lm/W
Lumen main.fact.at end of nom.life time	0.70
Light color (designation)	Daylight
Color temperature	6500 K
Color rendering index Ra	80
Light color	865
Standard deviation of color matching	≤6 sdcm

Light technical data

Beam angle	200 °
Starting time	0.5 s

Dimensions & Weight

Overall length	103.00 mm
Diameter	58.00 mm
Maximum diameter	58 mm
Product weight	24.00 g

Temperatures & operating conditions

Ambient temperature range	-20+40 °C

Lifespan

Additional product data

Base (standard designation)	B22d
Mercury content	0.0 mg
Mercury-free	Yes
Product remark	All technical parameters apply to the entire lamp / Due to the complex production process for light-emitting diodes, the typical values shown for the technical LED parameters are purely statistical values that do not necessarily match the actual technical parameters of each individual product, which can vary from the typical value

Capabilities

Dimmable		No									

Country-specific categorizations

Order reference

LECO CLA7W/8652

Energy labelling regulation data acc EU 2019/2015

Light source cap-type (or other electric interface)	B22d
Length	103.00 mm
Height	58.00 mm
Width	58.00 mm

DOWNLOAD DATA

Photometric and lighting design files	Document name
IES file (IES)	LED ECO CLA40 7W

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075246270	Folding box 1	62 mm x 62 mm x 112 mm	39.00 g	0.43 dm ³
4058075246287	Bundle 10	620 mm x 62 mm x 112 mm	395.00 g	4.31 dm ³
4099854078613	Bundle 10	280 mm x 112 mm x 104 mm	347.00 g	3.26 dm ³
4058075246294	Shipping box 100	637 mm x 332 mm x 253 mm	4678.00 g	53.51 dm ³

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4099854078620	Shipping box 100	574 mm x 294 mm x 233 mm	4115.00 g	39.32 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.