

# PRODUCT DATASHEET HE SL 21 W/830

SMARTLUX® T5 HE® | Tubular fluorescent lamps 16 mm, high efficiency






# TECHNICAL DATA

# Electrical data

| Nominal wattage                     | 21 W    |
|-------------------------------------|---------|
| Construction wattage                | 20.60 W |
| Nominal voltage                     | 220 V   |
| Rated lamp efficacy (HF data 25 °C) | 92      |

# Photometrical data

| Luminous efficacy         90 lm/W           Luminous flux at 25 °C         1900 lm           Luminous flux at 35 °C         2100 lm           Color temperature         3000 K           Color rendering index Ra         280           Light color         830           Rated LLMF at 2,000 h         0.95           Rated LLMF at 6,000 h         0.91           Rated LLMF at 8,000 h         0.90           Rated LLMF at 12,000 h         0.90           Rated LLMF at 16,000 h         0.90           Rated LLMF at 20,000 h         0.90           Rated LLMF at 9,000 h         0.90 |                                     | ,       |
|--|-------------------------------------|---------|
| Luminous flux at 25 °C       1900 lm         Luminous flux at 35 °C       2100 lm         Color temperature       3000 K         Color rendering index Ra       ≥80         Light color       830         Rated LLMF at 2,000 h       0.95         Rated LLMF at 4,000 h       0.92         Rated LLMF at 6,000 h       0.91         Rated LLMF at 8,000 h       0.90         Rated LLMF at 12,000 h       0.90         Rated LLMF at 16,000 h       0.90         Rated LLMF at 20,000 h       0.90         Rated LLMF at 20,000 h       0.90  | Luminous flux                       | 1900 lm |
| Luminous flux at 35 °C       2100 lm         Color temperature       3000 K         Color rendering index Ra       ≥80         Light color       830         Rated LLMF at 2,000 h       0.95         Rated LLMF at 4,000 h       0.92         Rated LLMF at 6,000 h       0.91         Rated LLMF at 8,000 h       0.90         Rated LLMF at 12,000 h       0.90         Rated LLMF at 16,000 h       0.90         Rated LLMF at 16,000 h       0.90         Rated LLMF at 20,000 h       0.89   | Luminous efficacy                   | 90 lm/W |
| Color temperature       3000 K         Color rendering index Ra       ≥80         Light color       830         Rated LLMF at 2,000 h       0.95         Rated LLMF at 4,000 h       0.92         Rated LLMF at 6,000 h       0.91         Rated LLMF at 8,000 h       0.90         Rated LLMF at 12,000 h       0.90         Rated LLMF at 16,000 h       0.90         Rated LLMF at 20,000 h       0.89  | Luminous flux at 25 °C              | 1900 lm |
| Color rendering index Ra       ≥80         Light color       830         Rated LLMF at 2,000 h       0.95         Rated LLMF at 4,000 h       0.92         Rated LLMF at 6,000 h       0.91         Rated LLMF at 8,000 h       0.90         Rated LLMF at 12,000 h       0.90         Rated LLMF at 16,000 h       0.90         Rated LLMF at 20,000 h       0.89   | Luminous flux at 35 °C              | 2100 lm |
| Light color       830         Rated LLMF at 2,000 h       0.95         Rated LLMF at 4,000 h       0.92         Rated LLMF at 6,000 h       0.91         Rated LLMF at 8,000 h       0.90         Rated LLMF at 12,000 h       0.90         Rated LLMF at 16,000 h       0.90         Rated LLMF at 20,000 h       0.90         Rated LLMF at 20,000 h       0.90  | Color temperature                   | 3000 K  |
| Rated LLMF at 2,000 h       0.95         Rated LLMF at 4,000 h       0.92         Rated LLMF at 6,000 h       0.91         Rated LLMF at 8,000 h       0.90         Rated LLMF at 12,000 h       0.90         Rated LLMF at 16,000 h       0.90         Rated LLMF at 20,000 h       0.90  | Color rendering index Ra            | ≥80     |
| Rated LLMF at 4,000 h       0.92         Rated LLMF at 6,000 h       0.91         Rated LLMF at 8,000 h       0.90         Rated LLMF at 12,000 h       0.90         Rated LLMF at 16,000 h       0.90         Rated LLMF at 20,000 h       0.89   | Light color                         | 830     |
| Rated LLMF at 6,000 h       0.91         Rated LLMF at 8,000 h       0.90         Rated LLMF at 12,000 h       0.90         Rated LLMF at 16,000 h       0.90         Rated LLMF at 20,000 h       0.89  | Rated LLMF at 2,000 h               | 0.95    |
| Rated LLMF at 8,000 h       0.90         Rated LLMF at 12,000 h       0.90         Rated LLMF at 16,000 h       0.90         Rated LLMF at 20,000 h       0.89   | Rated LLMF at 4,000 h               | 0.92    |
| Rated LLMF at 12,000 h       0.90         Rated LLMF at 16,000 h       0.90         Rated LLMF at 20,000 h       0.89  | Rated LLMF at 6,000 h               | 0.91    |
| Rated LLMF at 16,000 h         0.90           Rated LLMF at 20,000 h         0.89  | Rated LLMF at 8,000 h               | 0.90    |
| Rated LLMF at 20,000 h 0.89  | Rated LLMF at 12,000 h              | 0.90    |
|  | Rated LLMF at 16,000 h              | 0.90    |
| Rated lamp efficacy (HF data 25 °C) 92   | Rated LLMF at 20,000 h              | 0.89    |
|  | Rated lamp efficacy (HF data 25 °C) | 92      |



# Dimensions & Weight

| Overall length                              | 849.00 mm |
|---|-----------|
| Length with base excl. base pins/connection | 849,00 mm |

| Diameter   | 16.0 mm                           |
|--|-----------------------------------|
| Diameter   | 16,0 mm                           |
| Tube diameter  | 16 mm                             |
| Maximum diameter   | 16 mm                             |
| Product weight   | 65.00 g                           |
| Temperatures & operating conditions  |                                   |
| Rated ambient temp.w.max.luminous  | 35.0 °C                           |
| Lifespan   |                                   |
| Rated lamp survival factor at 2,000 h  | 0.99                              |
| Rated lamp survival factor at 4,000 h  | 0.99                              |
| Rated lamp survival factor at 6,000 h  | 0.99                              |
| Rated lamp survival factor at 8,000 h  | 0.99                              |
| Rated lamp survival factor at 12,000 h   | 0.99                              |
| Rated lamp survival factor at 16,000   | 0.90                              |
| Rated lamp survival factor at 20,000 h   | 0.50                              |
| Operation mode LLMF/LSF  | HF                                |
| Additional product data  |                                   |
| Base (standard designation)  | G5                                |
| Mercury content  | 1.2 mg                            |
| Capabilities   |                                   |
|  |                                   |
| Suitable for indoor  | Yes                               |
| Suitable for indoor  Certificates & Standards  | Yes                               |
|  | Yes A+                            |
| Certificates & Standards   |                                   |
| Certificates & Standards  Energy efficiency class  | A+                                |
| Certificates & Standards  Energy efficiency class  Energy consumption  | A+                                |
| Certificates & Standards  Energy efficiency class  Energy consumption  Country-specific categorizations  | A+<br>23.10 kWh/1000h             |
| Certificates & Standards  Energy efficiency class  Energy consumption  Country-specific categorizations  Order reference   | A+<br>23.10 kWh/1000h             |
| Certificates & Standards  Energy efficiency class  Energy consumption  Country-specific categorizations  Order reference  Energy labelling regulation data acc EU 2019/2015  | A+ 23.10 kWh/1000h  HE 21W/830 SL |
| Certificates & Standards  Energy efficiency class  Energy consumption  Country-specific categorizations  Order reference  Energy labelling regulation data acc EU 2019/2015  Light source cap-type (or other electric interface) | A+ 23.10 kWh/1000h  HE 21W/830 SL |

### DOWNLOAD DATA

| Photometric and lighting design files | Document name |
|---------------------------------------|---------------|
| Spectral power distribution           | 349617_FL_830 |

# LOGISTICAL DATA

| Product code  | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume                |
|---------------|------------------------------|--------------------------------------|--------------|-----------------------|
| 4008321339478 | Sleeve<br>1                  | 863 mm x 18 mm x 18 mm               | 80.00 g      | 0.28 dm <sup>3</sup>  |
| 4008321339485 | Shipping box<br>50           | 899 mm x 204 mm x 123 mm             | 5970.00 g    | 22.56 dm <sup>3</sup> |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

#### **DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.