

PRODUCT DATASHEET HE SL 21 W/830

SMARTLUX® T5 HE® | Tubular fluorescent lamps 16 mm, high efficiency






TECHNICAL DATA

Electrical data

Nominal wattage	21 W
Construction wattage	20.60 W
Nominal voltage	220 V
Rated lamp efficacy (HF data 25 °C)	92

Photometrical data

1900 lm
90 lm/W
1900 lm
2100 lm
3000 K
≥80
830
0.95
0.92
0.91
0.90
0.90
0.90
0.89
92



Dimensions & Weight

Overall length	849.00 mm
Length with base excl. base pins/connection	849,00 mm

Diameter	16.0 mm
Diameter	16,0 mm
Tube diameter	16 mm
Maximum diameter	16 mm
Product weight	65.00 g
Temperatures & operating conditions	
Rated ambient temp.w.max.luminous	35.0 °C
Lifespan	
Rated lamp survival factor at 2,000 h	0.99
Rated lamp survival factor at 4,000 h	0.99
Rated lamp survival factor at 6,000 h	0.99
Rated lamp survival factor at 8,000 h	0.99
Rated lamp survival factor at 12,000 h	0.99
Rated lamp survival factor at 16,000	0.90
Rated lamp survival factor at 20,000 h	0.50
Operation mode LLMF/LSF	HF
Additional product data	
Base (standard designation)	G5
Mercury content	1.2 mg
Capabilities	
Suitable for indoor	Yes
Suitable for indoor Certificates & Standards	Yes
	Yes A+
Certificates & Standards	
Certificates & Standards Energy efficiency class	A+
Certificates & Standards Energy efficiency class Energy consumption	A+
Certificates & Standards Energy efficiency class Energy consumption Country-specific categorizations	A+ 23.10 kWh/1000h
Certificates & Standards Energy efficiency class Energy consumption Country-specific categorizations Order reference	A+ 23.10 kWh/1000h
Certificates & Standards Energy efficiency class Energy consumption Country-specific categorizations Order reference Energy labelling regulation data acc EU 2019/2015	A+ 23.10 kWh/1000h HE 21W/830 SL
Certificates & Standards Energy efficiency class Energy consumption Country-specific categorizations Order reference Energy labelling regulation data acc EU 2019/2015 Light source cap-type (or other electric interface)	A+ 23.10 kWh/1000h HE 21W/830 SL

DOWNLOAD DATA

Photometric and lighting design files	Document name
Spectral power distribution	349617_FL_830

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4008321335463	Sleeve 1	863 mm x 18 mm x 18 mm	80.00 g	0.28 dm ³
4052899046702	Shipping box 20	891 mm x 104 mm x 88 mm	2283.00 g	8.15 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.