

# PRODUCT DATASHEET HE SL 14 W/827

SMARTLUX® T5 HE® | Tubular fluorescent lamps 16 mm, high efficiency






# TECHNICAL DATA

# Electrical data

Nominal wattage	14 W
Construction wattage	14.00 W
Nominal voltage	220 V
Rated lamp efficacy (HF data 25 °C)	86

# Photometrical data

Luminous flux	1200 lm
Luminous efficacy	85 lm/W
Luminous flux at 25 °C	1200 lm
Luminous flux at 35 °C	1350 lm
Color temperature	2700 K
Color rendering index Ra	≥80
Light color	827
Rated LLMF at 2,000 h	0.95
Rated LLMF at 4,000 h	0.92
Rated LLMF at 6,000 h	0.91
Rated LLMF at 8,000 h	0.90
Rated LLMF at 12,000 h	0.90
Rated LLMF at 16,000 h	0.90
Rated LLMF at 20,000 h	0.89
Rated lamp efficacy (HF data 25 °C)	86



# Dimensions & Weight

Overall length	549.00 mm
Length with base excl. base pins/connection	549,00 mm

Diameter	16.0 mm
Diameter	16,0 mm
Tube diameter	16 mm
Maximum diameter	16 mm
Product weight	45.00 g
Temperatures & operating conditions	
Rated ambient temp.w.max.luminous	35.0 °C
Lifespan	
Rated lamp survival factor at 2,000 h	0.99
Rated lamp survival factor at 4,000 h	0.99
Rated lamp survival factor at 6,000 h	0.99
Rated lamp survival factor at 8,000 h	0.99
Rated lamp survival factor at 12,000 h	0.99
Rated lamp survival factor at 16,000	0.90
Rated lamp survival factor at 20,000 h	0.50
Operation mode LLMF/LSF	HF
Additional product data	
Base (standard designation)	G5
Mercury content	1.2 mg
Capabilities	
Suitable for indoor	Yes
Certificates & Standards	
Energy efficiency class	A+
	A+ 15.40 kWh/1000h
Energy efficiency class	
Energy efficiency class Energy consumption	
Energy efficiency class  Energy consumption  Country-specific categorizations	15.40 kWh/1000h
Energy efficiency class  Energy consumption  Country-specific categorizations  Order reference	15.40 kWh/1000h
Energy efficiency class  Energy consumption  Country-specific categorizations  Order reference  Energy labelling regulation data acc EU 2019/2015	15.40 kWh/1000h  HE 14W/827 SL
Energy efficiency class  Energy consumption  Country-specific categorizations  Order reference  Energy labelling regulation data acc EU 2019/2015  Light source cap-type (or other electric interface)	15.40 kWh/1000h  HE 14W/827 SL  G5

### DOWNLOAD DATA

Photometric and lighting design files	Document name
Spectral power distribution	349636_FL_827

# LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4008321338365	Sleeve 1	563 mm x 18 mm x 18 mm	55.00 g	0.18 dm <sup>3</sup>
4008321338372	Shipping box 50	600 mm x 204 mm x 123 mm	2992.00 g	15.06 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

#### **DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.