

PRODUCT DATASHEET L 36 W/5400 K

LUMILUX® T8 | Tubular fluorescent lamps 26 mm, with G13 bases



Areas of application

- Public buildings
- Office lighting
- Industry
- Shops
- Supermarkets and department stores
- Street lighting
- Outdoor applications only in suitable luminaires

Product benefits

- Proven lamp technology

Product features

- Very good lumen maintenance: 90 % throughout the service lifetime of the lamp
- Good color rendering index
- Dimmable



TECHNICAL DATA

Electrical data

Nominal wattage	36 W	
Construction wattage	36.00 W	
Rated lamp efficacy (HF data 25 °C)	Under clarification by authority and standardization body	

Photometrical data

Luminous flux	3300 lm
Luminous efficacy	92 lm/W
Luminous flux at 25 °C	3300 lm
Color temperature	5400 K
Color rendering index Ra	80
Light color	854
Rated lamp efficacy (HF data 25 °C)	Under clarification by authority and standardization body

Dimensions & Weight

Overall length	1200.00 mm
Length with base excl. base pins/connection	1200 mm
Diameter	26.00 mm
Tube diameter	26 mm
Product weight	176.00 g

Lifespan

S	Service life	18000 h ¹⁾

1) With preheat ECG

Additional product data

Base (standard designation)	G13
Mercury content	2.5 mg

Capabilities

Dimmable Yes

Country-specific categorizations

ILCOS	FD-36/850-E-G13-26/1200
Order reference	L 36W/850LUMILU

Energy labelling regulation data acc EU 2019/2015

00.00 mm
00 mm
00 mm
0

Safety advice

- In case of lamp breakage: www.ledvance.com/brokenlamp

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4008321164957	Sleeve 1	1,215 mm x 29 mm x 29 mm	0.20 g	1.02 dm ³
4008321164964	Shipping box 25	1,241 mm x 151 mm x 153 mm	5.30 g	28.67 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.