

TECHNICAL DATA

Electrical data

| | |
|------------------------|-------------|
| Nominal wattage | 288.00 W |
| Nominal output power | 120...240 W |
| Nominal voltage | 12...24 V |
| Nominal output voltage | 12...24 V |
| Type of current | DC |
| Mains frequency | 50...60 Hz |

Dimensions & Weight



| | |
|----------------|----------|
| Length | 97.00 mm |
| Width | 33.00 mm |
| Height | 18.00 mm |
| Product weight | 49.00 g |

Colors & materials

| | |
|---------------|-------|
| Product color | White |
|---------------|-------|

Temperatures & operating conditions

| | |
|---------------------------|--------------|
| Ambient temperature range | -30...+55 °C |
|---------------------------|--------------|

Capabilities

| | |
|-------------------|-----|
| Dimmable | Yes |
| Dimming interface | PWM |

Certificates & Standards

| | |
|--------------------|------|
| Protection class | I |
| Type of protection | IP20 |

LOGISTICAL DATA

| | |
|------------------------------|--------------|
| Temperature range at storage | -30...+55 °C |
|------------------------------|--------------|

DOWNLOAD DATA

LOGISTICAL DATA

| Product code | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume |
|---------------|------------------------------|--------------------------------------|--------------|----------------------|
| 4058075359789 | Folding box 1 | 39 mm x 27 mm x 116 mm | 58.00 g | 0.12 dm ³ |
| 4058075359796 | Shipping box 10 | 144 mm x 120 mm x 88 mm | 634.00 g | 1.52 dm ³ |
| 4058075383814 | Shipping box 120 | | | |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.