

PRODUCT DATASHEET LED Value Slim Downlight 15 W/6500 K

LED VALUE SLIM DOWNLIGHT | Flat downlight luminaires



Areas of application

- Corridors, entrance areas
- Foyers
- Elevators
- Retail

Product benefits

- Die-cast aluminum housing for improved heat dissipation
- No light can escape at the back of the luminaires thanks a special cover
- Elegant design

Product features

- Product color: white
- $-\,$ Available with color temperature: 3,000 K, 4,000 K, 6,500 K
- Color rendering index R_a : > 80
- High color consistency: ≤ 6 SDCM
- Luminaire efficacy: up to 89 lm/W
- Type of protection: IP20
- Lifetime (L70/B50): up to 30,000 h
- Protection class: II
- Uniform illumination



TECHNICAL DATA

Electrical data

Nominal wattage	15.00 W
Nominal voltage	220240 V
Mains frequency	5060 Hz
Power factor λ	0.50
Protection class	II

Photometrical data

Luminous flux	1200 lm
Luminous efficacy	80 lm/W
Color temperature	6500 K
Light color (designation)	Daylight
Color rendering index Ra	80
Standard deviation of color matching	≤6 sdcm
Beam angle	120 °

Dimensions & Weight

Diameter	170.00 mm
Height	20.00 mm
Product weight	220.00 g

LDVAL SLIM Downlight RD 150 15W

Materials & Colors

Product color	White
Housing color	White
Body material	Aluminum
Cover material	Plastic

Mercury content	0.0 mg		
Application & Mounting			
Ambient temperature range	-10+50 °C		
Temperature range at storage	-20+70 °C		
Type of protection	IP20		
Dimmable	No		
Mounting type	Recessed		
Mounting location	Ceiling		
Application environment	Indoor		
Mounting diameter	150 mm		
Mounting depth	30 mm		
Replaceable light source	No		

Lifespan L70/B50 at 25 °C	30000 h ¹⁾
Number of switching cycles	25000

¹⁾ t[h]: L70 / B50 @ 25 °C (Ta), t[h]: L80 / B10 @ 25 °C (Ta), t[h]: L90 / B10 @ 25 °C (Ta)

Certificates & Standards

Replaceable light source (EPREL) Not replaceable

DOWNLOAD DATA

Photometric and lighting design files	Document name
IES file (IES)	LDVAL SLIMDL RD 150 15W 865

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075314092	Folding box 1	177 mm x 47 mm x 174 mm	287.00 g	1.45 dm ³
4058075314108	Shipping box 20	478 mm x 189 mm x 379 mm	6235.00 g	34.24 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.