

# PRODUCT DATASHEET LED SPOT 3 W 6500 K 38 °

LED SPOT LIGHT | LED spotlights



### Areas of application

- Hotels, apartments
- Offices

#### Product benefits

- Low flicker light thanks to special electronic control gear

#### **Product features**

- Plastic coating aluminum housing
- Beam angle:  $38^{\circ}$
- $-\,$  Color rendering index  $R_{a}\!\!:\,80$
- Power factor: 0.5
- Initial color consistency: < 5 SDCM
- Lifetime up to 15,000 h
- Type of protection: IP20
- CCC marked, CB test certificate



## TECHNICAL DATA

#### Electrical data

Nominal wattage	3.00 W
Nominal voltage	220240 V
Mains frequency	5060 Hz
Nominal current	25.000 mA
Power factor $\lambda$	0.50
Protection class	II
Operating mode	Integrated LED driver

#### Photometrical data

Luminous flux	255 lm
Luminous efficacy	85 lm/W
Color temperature	6500 K
Light color (designation)	Daylight
Color rendering index Ra	≥80
Standard deviation of color matching	≤6 sdcm
Beam angle	38 °

# Dimensions & Weight

Diameter	82.00 mm
Height	40.00 mm
Product weight	56.00 g



# Materials & Colors

Product color	White	
Housing color	White	
Body material	Polybutylene terephthalate (PBT)	
Cover material	Polycarbonate (PC)	

Mercury content	0.0 mg			
Application & Mounting				
Ambient temperature range	-20+35 °C			
Temperature range at storage	-20+70 °C			
Type of connection	Cable, 2-pole			
Type of protection	IP20			
Dimmable	No			
Mounting type	Recessed			
Mounting location	Ceiling			
Application environment	Indoor			
Mounting diameter	70,0 mm			
Mounting depth	70 mm			
Replaceable light source	No			
Lifespan				
Lifespan L70/B50 at 25 °C	15000 h <sup>1)</sup>			

<sup>1)</sup> t[h]: L70 / B50 @ 25 °C (Ta), t[h]: L80 / B10 @ 25 °C (Ta), t[h]: L90 / B10 @ 25 °C (Ta)

#### Certificates & Standards

Number of switching cycles

Replaceable light source (EPREL)	Not replaceable
----------------------------------	-----------------

30000

# LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075323889	Folding box 1	83 mm x 83 mm x 52 mm	72.00 g	0.36 dm <sup>3</sup>
4058075323896	Shipping box 24	350 mm x 265 mm x 133 mm	2113.00 g	12.34 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

#### **DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.