

# PRODUCT DATASHEET LED WALL WASHER 36 W 20 ° x 45 ° 500 mm RGB

## LED WALLWASHER RGB | LED outdoor luminaires with RGB



## Areas of application

- Architectural lighting
- Facade lighting

#### **Product benefits**

- High quality lens made of polycarbonate (PC), secondary optics with tempered glass cover
- Flexibility and convenience in use thanks to adjustable mounting bracket

## **Product features**

- Extruded aluminum housing and die-cast aluminum end caps
- Available in two lengths: 500 mm and 1000 mm
- RGB color control
- Type of protection: IP66
- Impact resistance: IK05
- Lifetime (L70/B50): up to 30,000 h
- With CQC certificate
- Certificate: CB



82 02, 2025, 23:55:19 LED WALL WASHER 36 W 20 ° x 45 ° 500 mm RGB

#### **TECHNICAL DATA**

## Electrical data

Nominal wattage	36.00 W
Nominal voltage	24 V
Nominal current	1500.000 mA
Protection class	III

#### Photometrical data

Luminous flux	540 lm
Luminous efficacy	15 lm/W
Light color (designation)	RGB
Color rendering index Ra	> 80
Standard deviation of color matching	≤5 sdcm
Beam angle	20 ° x 45 °

## **Dimensions & Weight**

Length	500.00 mm
Width	70.00 mm
Height	81.70 mm
Product weight	1550.00 g
Cable length	200 mm



24/36W/RGB

## Materials & Colors

Product color	Silver
Housing color	Silver
Body material	Glass Aluminum
Cover material	CLEAR GLASS
Mercury content	0.0 mg

## **Application & Mounting**

Ambient temperature range	-20+50 °C	
Temperature range at storage	-20+70 °C	
Type of connection	Plug, quick disconnect	
Type of protection	IP66	
Protection class IK (shock resistance)	IK05	
Dimmable	Yes	
Type of dimming	DMX	
Mounting type	Surface	
Mounting location	Wall	
Application environment	Outdoor	
Replaceable light source	No	

#### Lifespan

Lifespan L70/B50 at 25 °C	30000 h <sup>1)</sup>
Number of switching cycles	30000

1) t[h]: L70 / B50 @ 25 °C (Ta), t[h]: L80 / B10 @ 25 °C (Ta), t[h]: L90 / B10 @ 25 °C (Ta)

## Emergency lighting

Type of emergency operation test None	
---------------------------------------	--

#### LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075335165	Folding box 1	510 mm x 85 mm x 75 mm	1660.00 g	3.25 dm <sup>3</sup>
4058075335172	Shipping box 4	530 mm x 185 mm x 180 mm	7142.00 g	17.65 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

## DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.