

PRODUCT DATASHEET VALUE CEILING 10 W 3000 K GEN3

LED VALUE CEILING | Wall and ceiling luminaires



Areas of application

- Corridors
- Entrances / Hallways

Product benefits

- Direct connection to AC power supply thanks to integrated control gear
- Long lifetime thanks to LED technology
- Mercury-free technology
- Uniform room illumination

Product features

- Beam angle: 120°
- Color rendering index R_a : ≥ 80
- Available with color temperature: 3,000 K, 4,000 K, 6,500 K



TECHNICAL DATA

Electrical data

Nominal wattage	10.00 W
Nominal voltage	220240 V
Mains frequency	5060 Hz
Nominal current	110.000 mA
Power factor λ	> 0.5
Protection class	I
Operating mode	Integrated LED driver

Photometrical data

Luminous flux	760 lm
Luminous efficacy	76 lm/W
Color temperature	3000 K
Light color (designation)	Warm White
Color rendering index Ra	≥80
Standard deviation of color matching	≤6 sdcm
Beam angle	120°

Dimensions & Weight

Diameter	255.00 mm
Height	73.00 mm
Product weight	358.00 g





LEDVAL CEILING 10W Gen3

Materials & Colors

Product color	White	
Housing color	White	
Body material	Polymethylmethacrylate (PMMA)	
Cover material	Polymethylmethacrylate (PMMA)	

Mercury content	0.0 mg	
Application & Mounting		
Ambient temperature range	-20+40 °C	
Temperature range at storage	-20+70 °C	
Type of connection	Plug, quick disconnect	
Type of protection	IP20	
Dimmable	No	
Mounting type	Surface	
Mounting location	Ceiling	
Application environment	Indoor	
Replaceable light source	No	

Lifespan

Lifespan L70/B50 at 25 °C	15000 h ¹⁾
Number of switching cycles	30000

¹⁾ t[h]: L70 / B50 @ 25 °C (Ta), t[h]: L80 / B10 @ 25 °C (Ta), t[h]: L90 / B10 @ 25 °C (Ta)

Certificates & Standards

Replaceable light source (EPREL)	Not replaceable
----------------------------------	-----------------

DOWNLOAD DATA

Photometric and lighting design files		Document name	
	IES file (IES)	Ceiling10-20W SP_10W 3000K IP20_44	

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075310100	Folding box 1	277 mm x 82 mm x 278 mm	519.00 g	6.31 dm ³
4058075310117	Shipping box 5	426 mm x 292 mm x 305 mm	3293.00 g	37.94 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.