

# PRODUCT DATASHEET LED VALUE HE BATTEN 9.60 W 6500 K 900 mm

LED VALUE HE BATTEN | LED batten luminaires with high luminous efficacy



#### Areas of application

- Contour lighting
- Cove lighting
- Shelf lighting
- Backlighting
- Indoor applications

#### Product benefits

- Homogeneous light output
- Flexible application due to a wide range of available lengths of 300 to 1200 mm.
- Mercury-free technology

#### **Product features**

- Uniform illumination
- Available with color temperature: 3,000 K, 4,000 K, 6,500 K
- Beam angle: 120°
- Connection with 2-pin plug connection
- Lifetime (L70/B50): up to 20,000 h
- High luminous efficacy: up to 100 lm/W
- Power factor: > 0.9
- Certificate: CB




### TECHNICAL DATA

#### Electrical data

Nominal wattage	9.60 W
Nominal voltage	220240 V
Mains frequency	5060 Hz
Nominal current	43.000 mA
Power factor $\lambda$	0.90
Protection class	II

# Photometrical data

Luminous flux	960 lm
Luminous efficacy	100 lm/W
Color temperature	6500 K
Light color (designation)	Daylight
Color rendering index Ra	80
Standard deviation of color matching	≤5 sdcm
Beam angle	120 °



LDVAL BAT HE 900 9.6W G3 24X1 EN LEDV

# Dimensions & Weight

Length	885.00 mm
Width	22.20 mm
Height	32.50 mm
Product weight	107.00 g



#### Materials & Colors

Product color	White
Housing color	White
Body material	Polycarbonate (PC)
Cover material	Polycarbonate (PC)
Mercury content	0.0 mg

### **Application & Mounting**

Ambient temperature range	-20+35 °C
Temperature range at storage	-20+70 °C
Type of protection	IP20
Dimmable	No
Mounting type	Surface
Mounting location	Ceiling
Replaceable light source	No

#### Certificates & Standards

Replaceable light source (EPREL)	Not replaceable
riepiaceable light source (El Field)	Not replaceable

### Accessories Optional

Product image	oduct image Product name	
	LDV BAT POWER CABLE LDVAL BAT POWER	4058075282001
	LDV BAT CONNECT CABLE LDVAL BAT CONNE	4058075282018

#### **EQUIPMENT / ACCESSORIES**

- Connection cable included
- Accessories for connection cable and power cable available

#### **DOWNLOAD DATA**

Photometric and lighting design files	Document name	
IES file (IES)	LDVAL BAT HE 900 9.6W G3 24X1 EN LEDV	
Light distribution curve type polar LDVAL BAT HE 900 9.6W G3 24X1 EN LEDV		

#### LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075414525	Folding box	950 mm x 23 mm x 34 mm	162.00 g	0.73 dm <sup>3</sup>
4058075414532	Shipping box 24	968 mm x 155 mm x 155 mm	4534.00 g	23.26 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

#### **DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.